



FABRIC ROLL DUCT CONNECTOR



Elgen Manufacturing
300 Murray Hill Parkway, East Rutherford, NJ 07073
(800) 503-9805 :: www.elgenmfg.com

DESCRIPTION

Elgen's Fabric Roll duct connector eliminates duct system noises and vibrations. This is done with an airtight flexible connection consisting of a fabric that attaches to sheet metal on both sides.

TECHNICAL INFORMATION

	Vinlon	Neoprene	Hypalon	Silguard	Teflon	40 oz Neoprene	Super High Temp
Temp Range	-40 F to 265 F	-40 F to 200 F	-50 F to 300 F	-75 F to 500 F	-75 F to 500 F	-40 F to 285 F	-40 F to 1800 F
Color	Black	Black	White	White	Gray	Black	Gray/White
Weight SQ/YD	22	32	24	18	18	40	36
Tear Strength	100/100	25/25	20/20	50/40	60/40	17/12	60/60
Tensile Strength	300/300	500/500	350/250	200/150	400/300	630/465	480/330
Features	High Tear Strength, High Abrasion, Low Smoke, Extremely Flexible	Airtight Resistance to Acids, Gasoline & Grease, General Purpose	Excellent Acid, Weather, UV, Mildew & Ozone Resistance, High Abrasion, Resistant to Grease	High Temp., Very Low Smoke, Flame, Water, & Oil Resistant	High Temp. & Acid Resistant, Best Overall Fabric		

All items are Flame Resistant

PRODUCT SPECIFICATIONS

All Elgen fabrics are designed to meet NFPA-701 (formerly UL-214)

Elgen Vinlon fabric meets UL-723 and NFPA-701

All Elgen fabrics are designed to meet NFPA-90A and 90B

All fabrics are water proof and airtight

All fabrics have flame retardant coatings

PACKAGING

Size	FT Per Box
6" - 10" - 12"	100'

150' Roll Available Upon Request

PRODUCT GUARANTEE

Elgen's Fabric Roll Duct Connector guaranteed by Elgen Manufacturing for defective material.